




# CAPTOR<sup>®</sup>

Electronic Security

## CP 5400

Dome camera with infrared, valid for exterior. Technology 4 in 1 ( HDTVI / HDCVI / AHD / CVBS) Range 1080p PRO

- \* Using high performance IMX335 image sensor , with 5.0 MP
- \* Support coaxial transmission for HD video and control signal
- \* Support common 75-5 similar coaxial cable lossless taransmission up to 300 meters above
- \* High speed, long distance real-time transmission
- \* Support ICR switching
- \* Support UTC function
- \* With Dip switch Husing
- \* IP 65 Metal Dome Husing
- \* White color



### Specification

|                      |                        |                |
|----------------------|------------------------|----------------|
| Model                | <b>CP 5400</b>         |                |
| Specification        | 5 MP 4 IN 1 HD Camera  |                |
| Sensor               | 1/2.8" IMX335          |                |
| ISP                  | FH8538M                |                |
| System               | PAL / NTSC             |                |
| Effective Pixel      | 2560* 1944             |                |
| SYNC.                | Internal               |                |
| Resolution           | 5 Megapixel            |                |
| Video.OUT            | AHD / TVI / CVI / CVBS |                |
| Minimum illumination | 0.01 Lux (F1.2)        |                |
| Gama Adjust          | 0.45                   |                |
| Electric Shutter     | 1/25s-1/10000s         | 1/30s-1/10000s |
| AE                   | GOBE/BLC               |                |
| WB                   | ATW/MWB                |                |
| DNR                  | 1/10                   |                |

|                       |                                                 |
|-----------------------|-------------------------------------------------|
| Lens                  | 3.6 MM                                          |
| IR series distance    | 12 PCS SMD LED , 15 M                           |
| Power supply          | DC12V , 600mA                                   |
| OSD Menu              | YES                                             |
| Day / Night           | Ext / AUTO / Color / MONO                       |
| Language              | Eng / chinese 1 / chinese 2 / Pycc / Ita / Port |
| Common                |                                                 |
| Operation temperature | -20 ~ +60°C                                     |
| Working humidity      | Relative Humidity less than 90% RH              |
| Power input           | DC 12 V ±20% -65mA                              |
| Dimension             | Ø 110×85mm                                      |
| Weight                | 380g                                            |