




**CAPTOR**<sup>®</sup>  
Electronic Security

## CP-7300 / 2MP

Bullet camera with infrared, valid for exterior. Technology 4 in 1 ( HDTV / HDCVI / AHD / CVBS) Range 1080p PRO

- \* Using high performance F23 image sensor , with 2.0 MP
- \* Support coaxial transmission for HD video and control signal
- \* Support common 75-5 similar coaxial cable lossless transmission up to 300 meters above
- \* High speed, long distance real-time transmission
- \* Support ICR switching
- \* With dip switch cable support switch output
- \* 3DNR function
- \* Ip66 Metal bullet housing
- \* Housing with black glass
- \* Black and white color



### Specification

Model	<b>CP7300</b>
Specification	2 Megapixel 4 IN 1 HD Camera
Sensor	1/2.9 F23"
ISP	FH8536H
System	PAL / NTSC
Effective Pixel	1920 * 1080
SYNC.	Internal
Resolution	2 Megapixel
Video.OUT	AHD / TVI / CVI / CVBS
Minimum illumination	0.01 Lux (F1.2)
S/N Ratio	48 dB(min)(AGC closed )
DWDR	CLOSE / OPEN
3DNR	AUTO / MANUAL ( 0- 10 )
AWB	GRAY WORLD / PRO / MWB
EXPOSURE MODE	GLOBAL / BLC

Lens	3.6 MM
IR series distance	18 PCS SMD LE , 20 M
Power supply	DC12V , 200mA
OSD Menu	YES
Day / Night	Ext / AUTO / Color / MONO
Language	Eng / chinese 1 / chinese 2 / Pycc / Espa / Pol / Ita / Port / JAP
Common	
Operation temperature	-10 ~ +55°c
Working humidity	Humidity less than 85% RH
Power input	DC 12 V ±1V
Dissipation Transmission	45 - 55 mA
Distance	75-5 300M
Dimension	165 (L) x 70 (W) x 70 (H) mm
Weight	282g

## Dimension

