



# CAPTOR®

Electronic Security

## CP-8000 Motorised



- \* 1/3" Sony© Exmor IMX323 CMOS Motorised HD Bullet Camera
- \* Horizontal: 220°, Vertical: 85°
- \* 2.7~13.5 mm 5 X Motorised Lens
- \* Matrix IR LEDs Scope 120 m



2.0  
Megapixel

1080P  
Resolution

HD  
Technology

2.7~13.5  
Autofocus  
Lens

### Specifications

Image sensor	1/3" Sony© Exmor IMX323 CMOS
DSP	NVP2441
Maximum resolution	2 Megapixel (1920x1080)
Video output	1 x BNC switchable HDTVI 2.0
Lens	Vari-focal Autofocus 2.7~13.5mm
Optical zoom	5 X
Minimum illumination	Colour: 0.1 Lux, BW: 0.01 Lux
Infrared lighting	0 Lux / Matrix IR LEDs (120 m)
Image improvements	3D-NR, BLC, AWB, AGC
Day / Night	Removable ICR mechanical filter (dual Day / Night)
Pan/Tilt Range	Horizontal: 220°, Vertical: 85°
Manual speed	Horizontal: 0° ~ 30°/sec, Vertical: 0° ~ 25°/sec
Preset positions	220, 1 auto-scan, 3 tour, 1 pattern
Communication	RS485, Pelco P / Pelco D / DH-SD
Power supply	DC 12 V / 15W
Temperature control	Automatic thermostat control
Degree of protection	Weatherproof IP66
Temp. operation	-40° C ~ 60° C
Dimensions	315 (d) x110 (w) x170 (h) mm
Weight	1000 g