



**CAPTOR**<sup>®</sup>  
Electronic Security

## CAPTOR CP 5600



Brand	CAPTOR
Image sensor	1/1" Progressive Scan CMOS
Maximum resolution	2 Megapixel (1080P/720P)
Main Stream rate	1080P/ 720P
Extra Stream rate	1080p / 704x256 (1 ~ 25 FPS)
Compression	H265 /H.264+ / H264 / MJPEG
Bitrate	32 Kbps ~ 16 Mbps
Lens Varifocale	2.8 mm ~ 12 mm
Minimum illumination	0.1 Lux (50 IRE ,F1.2,1/15s) Night , 1 Lux ( 50 IRE,F12 , 1/30 s Day
Image improvements	WDR, BLC, 3D-NR, AWB, Privacy Masking, ROI
Commande	Auto IRIS / P IRIS
Protocole	TCP ,UDP,ICMP,IGMP,SNMP,HTTPS,RTP,DHCP,NTP
Day / Night	OUI
Internal memory	MicroSD card 16 Go, Max 128 GB (pour fonction LPR )
Horloge	temps réel embarquée , client NTP
Alarms	4 inputs / 6 relay NO/NC
DéTECTANT mouvement	OUI

Communication Interface	1 x Ethernet 10/100/1000M BaseT
Remote access	Web browser, Safire Control Center Smartphone App and PC Software
Interoperability	ONVIF, PSIA, CGI
Authentication	Mot de pass
Power supply	POE , DC 12 V
Matériau fabriqué	Structure Inoxydable
Matériau fabriqué	Structure Inoxydable pour des milieux sahariens
Chauffage	OUI
Ventilateur	OUI
Pare-soleil	OUI
Passage de câble	Via le support caisson
Degree of protection	Weatherproof IP66
Temp. operation	-30° C ~ +60° C
Le poids	1150 g