






**CAPTOR**<sup>®</sup>  
ELECTRONIC SECURITY

## CP - 5300

Plastic dome camera with infrared, valid for exterior, Technology 4 in 1 ( HDTVI / HDCVI / AHD / CVBS ) Range 1080p PRO

- Using high performance F23 image sensor, with 2.0 MP
- Support coaxial transmission for HD video and control signal
- Support common 75-5 similar coaxial cable lossless transmission up to 300 meters cable above
- High speed, long distance real-time transmission
- Support ICR switching
- With dip switch cable support switch output
- 3DNR function
- IP66 Metal bullet housing
- Housing with black glass
- Grey color



### Specification

Model	CP - 5300
Specification	2MP 4 IN 1 HD Camera
Sensor	1/2.9 F23"
ISP	FH8536H
System	PAL/NTSC
Effective Pixel	1920 * 1080
SYNC.	Internal
Resolution	2 Megapixel
Video.OUT	AHD / TVI / CVI / CVBS
Minimum illumination	0.01 Lux (F 1.2)
S/NRatio	48 dB(min)(AGC closed)
DWDR	CLOSE/OPEN
3DNR	AUTO/MANUAL (0-10)
AWB	GRAY WORLD/ PRO/MWB
EXPOSURE MODE	GLOBAL/BLC

Lens	3.6
IR series distance	18 PCS SMD LE, 20M
Power supply	DC12V, 200mA
OSD Menu	YES
Day / Nigh	Ext / Auto / Color / MONO
Language	eng / Chinese 1 /Chinese 2 /Pycc /Espa / Pol / Ita /Port /JAP
Common	Internal
Opertion temprature	-10 ~ +55°c
Working humidity	Humidity less than 85% RH
Power input	DC 12V ± 1V
Dissipation Transmission	48 dB(min)(AGC closed)
Distance	75-5 300M
Dimension	Ø 85*70mm
Weight	110g