



Model No.	CP 4004
system	
Master chip	MC6630
AD chip	2830
RAM	2G
Compression format	H.265
operating system	Embedded Linux operating system
video	
Input	4
Preview	4*5MN@20fps
Coding	4*5MN@12fps
Decoding	4*5MN@12fps
Channel mode	Support any channel mode combination (5MN analog + 5M digital)
VGA output	1080P
BNC output	Optional, not supported by default
HDMI output	1080P

Audio	
Audio Input	1
Audio output	1
Coaxial audio	4
Two-way intercom	support
Playback	
Number of real-time recording channels	4-way non-real-time
Video mode	Timing, manual, motion detection
The number of simultaneous playback	4
Search mode	Point-in-time search, calendar search, event search, channel search
Backup	
USB mobile hard disk, U disk	support
USB DVD burner	support
Format	H.26X、AVI
remote access	
Browser	Supports multiple web browsers
Client	Support VMS
APP	Support for iPhone, Android
storage	
HDD NO.	1
E-SATA	not support
Network	
Network port	10 / 100 Mbps Ethernet (RJ-45)
Powerful network services	supporting DHCP, PPPOE, FTP, DNS, DDNS, NTP, UPNP, Email, etc.(Except WIFI and 3G\4G modules are not supported)), complete supporting facilities (WEB, client, SDK), easily achieve interconnection and interoperability.
General	
Language	Simplified Chinese,Traditional Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Japanese, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek, Vietnamese,
remote control	support
power supply	DC 12V/2A ≤4W (Without Hard Disk)
Work Temperature	-10°C ~60°C
Working humidity	10% ~ 90% Humidity
Dimension(W×D×H)	255*212*45mm
Weight	1.5kg